



DRY CARGO HATCH SEALING TAPE

Heavy Duty – HD Standard Duty – SD

PRODUCT SPECIFICATION

DRY CARGO tape is manufactured in Great Britain and marketed internationally by Cullen, Metcalfe & Co Ltd. The tape was developed in the early 1970s, and has since been progressively upgraded to reflect the availability of enhanced raw materials.

DRY CARGO is produced in 20mtr rolls of bitumen compound coated onto polythene film and interleaved with release paper.

It is available in two distinct grades – Heavy Duty (HD) and Standard Duty (SD)

Technical Specification:	H.D.	S.D.
Nominal thickness:	2.7mm	1.6mm
Break strength:		
Longitudinal	7.0 N/mm	5.0 N/mm
Transverse	6.0 N/mm	5.8 N/mm
Adhesive Peel Strength to Steel	3.0 N/mm	3.0 N/mm
Service Temperature	-20>+65DegC	-20 + 65DegC

It is certified that **DRY CARGO** Marine Hatch Tapes are manufactured in Great Britain, and that all production procedures fully comply with all relevant Safety and Environmental procedures.

CULLEN METCALFE & Co Ltd,
sales@cullenmetcalfe.com. Tel +44 (0)1279 813442
Worldwide distributor of DRY CARGO tape